

219.3237**PLUG**

32A 3P+N+E 6h 346-415V 60Hz 50Hz
II 2GD Screw terminals Low
temperature [-50°C]



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)
EN 60079-0 (2018)
IEC 60079-0 (2017)
IEC 60079-31 (2013)
EN 60079-7 (2015)
EN 60309-4 (2007)
EN 60309-4/A1 (2012)
EN 60079-31 (2014)
EN 60079-7/A1 (2018)
IEC 60079-7 (2017)
EN 60079-1 (2014)
IEC 60079-1 (2014)
ATEX directive 2014/34/EU

Commercial Series	OPTIMA-EX[GD] Series
Synthetical description	PLUG
Mounting version	PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	32A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
-------------------------	--------

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP66
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Surface treatment contacts	Nickel-plated
Cable entry	CABLE GLAND
Ambient temperature Ta min	-50 °C
Ambient temperature Ta max	60 °C

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual
Instruction manual

■ OPTIONS & VARIOUS NOTES

Options	Low temperature [-50°C]
---------	-------------------------