

219.1636

PLUG
 16A 3P+E 6h 380-415V 60Hz 50Hz II
 2GD Screw terminals Low
 temperature [-50°C]



EN 60309-1 (1999)
 EN 60309-2 (1999)
 EN 60309-1/A1 (2007)
 EN 60309-1/A2 (2012)
 EN 60309-2/A1 (2007)
 EN 60309-2/A2 (2012)
 EN 60079-0 (2018)
 IEC 60079-0 (2017)
 IEC 60079-31 (2013)
 EN 60079-7 (2015)
 EN 60309-4 (2007)
 EN 60309-4/A1 (2012)
 EN 60079-31 (2014)
 EN 60079-7/A1 (2018)
 IEC 60079-7 (2017)
 EN 60079-1 (2014)
 IEC 60079-1 (2014)
 ATEX directive 2014/34/EU

| | |
|-------------------------|----------------------|
| Commercial Series | OPTIMA-EX[GD] Series |
| Synthetical description | PLUG |
| Mounting version | PORTABLE |

■ TECHNICAL CHARACTERISTICS

| | |
|-----------------------|-----------------|
| Rated current | 16A |
| Poles | 3P+E |
| Hour position | 6h |
| Rated voltage (range) | 250-400V |
| Rated voltage | 380-415V |
| Working frequency | 60Hz |
| | 50Hz |
| Terminals | Screw terminals |

■ EX CHARACTERISTICS

| | |
|-------------------------|--------|
| Group and categories EX | II 2GD |
|-------------------------|--------|

■ PHYSICAL CHARACTERISTICS

| | |
|----------------------------|---------------|
| Mounting version | PORTABLE |
| Colour | RED |
| Material | THERMOPLASTIC |
| Protection degree | Splash proof |
| Protection degree IP | IP66 |
| Types of available outlets | STRAIGHT |
| Contact material | CuZn (brass) |
| Surface treatment contacts | Nickel-plated |
| Cable entry | CABLE GLAND |
| Ambient temperature Ta min | -50 °C |
| Ambient temperature Ta max | 60 °C |

■ DOWNLOAD

Technical drawing [PDF]
 Technical drawing [DWG]
 Technical drawing [STP]
 Instruction manual
 Instruction manual

■ OPTIONS & VARIOUS NOTES

| | |
|---------|-------------------------|
| Options | Low temperature [-50°C] |
|---------|-------------------------|