

319.1646**CONNECTOR**

16A 3P+E 6h 380-415V 60Hz 50Hz II
2GD Screw terminals



EN 60079-31 (2014)
EN 60079-1 (2014)
EN 60079-7 (2015)
EN 60079-7/A1(2018)
EN 60079-0 (2018)
IEC 60079-31 (2013)
IEC 60079-1 (2014)
IEC 60079-0 (2017)
IEC 60079-7 (2017)
IEC 60079-31 (2022)

Low voltage direct. 2014/35/EU
ATEX directive 2014/34/EU

Commercial Series

OPTIMA-EX[GD] Series

Synthetical description

CONNECTOR

Mounting version

PORTABLE

■ TECHNICAL CHARACTERISTICS

Rated current	16A
Poles	3P+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	380-415V
Working frequency	60Hz
	50Hz
Terminals	Screw terminals

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
Modo protezione gas	Ex db eb IIC T3 Gb Ta-50/+60°C
Gas protection mode	Ex db eb IIC T4 Gb Ta-50/+50°C
Dust protection	Ex tb IIIC T85°C Db IP66

■ PHYSICAL CHARACTERISTICS

Mounting version	PORTABLE
Colour	RED
Material	THERMOPLASTIC
Protection degree	Splash proof
Protection degree IP	IP66
Protection degree IK	IK08
Types of available outlets	STRAIGHT
Contact material	CuZn (brass)
Cable entry	CABLE GLAND
Ambient temperature Ta min	-50 °C
Ambient temperature Ta max	60 °C

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual