

16A 3P+N+E 6h 346-415V 50Hz 60Hz
II 2GD 130X260MM_PAR Screw
terminals With mechanical interlock



ATEX directive 2014/34/EU

Commercial Series	ADVANCE-GRP[GD] Series
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING

Rated current	16A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

Group and categories EX II 2GD

Mounting version	SURFACE MOUNTING
Colour	RED
Material	GRP Glass Reinforced Polyester
Protection degree	Splash proof
Protection degree IP	IP66
Protection degree IK	IK10
Contact material	CuZn (brass)
Cable entry	1xM25
Working temperature	-40°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Ambient temperature Ta min	-35 °C
Ambient temperature Ta max	60 °C
Padlock	ø5mm

Flange	130X260MM_PAR
--------	---------------

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)
[Instruction manual](#)

Options	With mechanical interlock
1. The door is closed and the machine is in the 'standby' position. The operator presses the 'start' button. The machine starts to operate. 2. The operator presses the 'stop' button. The machine stops operating. 3. The operator presses the 'start' button again. The machine starts operating again.	1. The door is closed and the machine is in the 'standby' position. The operator presses the 'start' button. The machine starts to operate. 2. The operator presses the 'stop' button. The machine stops operating. 3. The operator presses the 'start' button again. The machine starts operating again.