

504.6387**INTERLOCKED SOCKET**

63A 3P+N+E 6h 346-415V 50Hz 60Hz
II 2GD 170X380MM_PAR Screw
terminals With mechanical interlock



EN 60309-1 (1999)
EN 60309-2 (1999)
EN 60309-1/A1 (2007)
EN 60309-1/A2 (2012)
EN 60309-2/A1 (2007)
EN 60309-2/A2 (2012)
EN 60079-0 (2018)
IEC 60079-0 (2017)
IEC 60079-31 (2013)
EN 60079-7 (2015)
EN 60309-4 (2007)
EN 60309-4/A1 (2012)
EN 60079-31 (2014)
EN 60079-7/A1 (2018)
IEC 60079-7 (2017)
EN 60079-1 (2014)
IEC 60079-1 (2014)
ATEX directive 2014/34/EU

Commercial Series	ADVANCE-GRP[GD] Series
Synthetical description	INTERLOCKED SOCKET
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	63A
Poles	3P+N+E
Hour position	6h
Rated voltage (range)	250-400V
Rated voltage	346-415V
Working frequency	50Hz
	60Hz
Terminals	Screw terminals

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
-------------------------	--------

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Colour	RED
Material	GRP Glass Reinforced Polyester
Protection degree	Splash proof
Protection degree IP	IP66
Protection degree IK	IK10
Contact material	CuZn (brass)
Cable entry	1xM40
Working temperature	-35°C/+60°C
GLOW WIRE	GW 960°C
Self-extinguishing UL94	V0
Padlock	ø6,3mm

■ DIMENSIONAL CHARACTERISTICS

Flange	170X380MM_PAR
--------	---------------

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]
Instruction manual
Instruction manual

■ OPTIONS & VARIOUS NOTES

Options	With mechanical interlock
---------	---------------------------