

591.PGE2004

SWITCH DISCONNECTOR
20A 3/4P IP66 160x160x90mm II 2GD
GENERAL GREY



EN 60079-31 (2014)
EN 60947-1/A1 (2011)
EN 60947-1 (2007)
EN 60947-3/A2 (2015)
EN 60947-3/A1 (2012)
EN 60947-1/A2 (2014)
EN 60079-0 (2018)
IEC 60079-0 (2017)
EN 60079-7 (2015)
IEC 60079-31 (2013)
EN 60947-3 (2009)
EN 60079-7/A1 (2018)
IEC 60079-7 (2017)
EN 60079-1 (2014)
IEC 60079-1 (2014)
ATEX directive 2014/34/EU

Commercial Series

ISOLATORS-EX[GD] Series

Synthetical description

SWITCH DISCONNECTOR

Type

GENERAL

■ TECHNICAL CHARACTERISTICS

Rated current	20A
---------------	-----

Poles	3/4P
-------	------

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
-------------------------	--------

■ PHYSICAL CHARACTERISTICS

Material	ENGINEERING PLASTIC
----------	---------------------

Protection degree IP	IP66
----------------------	------

Colour	GREY
--------	------

Ambient temperature Ta min	-35 °C
----------------------------	--------

Ambient temperature Ta max	60 °C
----------------------------	-------

■ DIMENSIONAL CHARACTERISTICS

Dimensions	160x160x90mm
------------	--------------

■ DOWNLOAD

[Technical drawing \[PDF\]](#)
[Technical drawing \[DWG\]](#)
[Technical drawing \[STP\]](#)
[Instruction manual](#)
[Instruction manual](#)