

592.R001-03-P

DP SWITCH
DP SWITCH 16AX
1xM20+2xM20 II 2GD



EN 60079-0 (2012)
EN 60079-31 (2014)
IEC 60079-31 (2013)
EN 60079-0/A11 (2013)
EN 60079-1 (2014)
EN 60079-7 (2015)
IEC 60079-1 (2014)
EN 60669-1 (2018)
IEC 60669-1 (2017)
IEC 60079-0 (2017)
IEC 60079-7 (2017)
EN 60079-7/A1(2018)
ATEX directive 2014/34/EU

Commercial Series	ROCKER-EX[GD] Series
Synthetical description	DP SWITCH
Mounting version	SURFACE MOUNTING

■ TECHNICAL CHARACTERISTICS

Rated current	16AX
Rated voltage	250V

■ EX CHARACTERISTICS

Group and categories EX	II 2GD
-------------------------	--------

■ PHYSICAL CHARACTERISTICS

Mounting version	SURFACE MOUNTING
Protection degree	Splash proof
Protection degree IP	IP66
Material	THERMOPLASTIC
Ambient temperature Ta min	-35
Ambient temperature Ta max	60

■ DOWNLOAD

Technical drawing [PDF]
Technical drawing [DWG]
Technical drawing [STP]

■ OPTIONS & VARIOUS NOTES

Notes	1xM20+2xM20
-------	-------------