







This item includes:

			
<b>Item No.: 221-412</b> Splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent	<b>Item No.: 221-413</b> Splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent	<b>Item No.: 221-415</b> Splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent	<b>Item No.: 221-2411</b> Inline splicing connector with levers; for all conductor types; max. 4 mm <sup>2</sup> ; 2-conductor; transparent housing; Transparent cover; Surrounding air temperature: max 85°C (T85); 4,00 mm <sup>2</sup> ; transparent

Notes

Safety management note

**NOTICE: Observe installation and safety instructions!**

- Only to be used by electricians!
- Do not work under voltage/load!
- Use only for proper use!
- Observe national regulations/standards/guidelines!
- Observe technical specifications for the products!
- Observe the number of permissible potentials!
- Do not use damaged/dirty components!
- Observe conductor types, cross-sections and strip lengths!
- Insert conductor until it hits the product's backstop!
- Use original accessories!

**To be sold only with installation instructions!**

Physical data	
Width	259 mm / 10.197 inches
Height	42 mm / 1.653 inches
Depth	106 mm / 4.173 inches



Material data	
Note (material data)	<a href="#">Information on material specifications can be found here</a>
Fire load	5.642 MJ
Weight	412.1 g

Commercial data	
ETIM 8.0	EC000446
PU (SPU)	1 pcs
Country of origin	DE
GTIN	4066966194883
Customs tariff number	85369010000

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads	
Environmental Product Compliance	
Compliance Search	
Environmental Product Compliance 887-803	