



ATLLED6/M3



Features

High performance LED batten for multi-purpose applications

Exceeds performance of T5 equivalents

Steel body construction with powder coat finish

Unique opal diffuser design for optimum performance and light distribution

Polycarbonate end caps

Instant light output with unlimited switching

Integral switch allows the installer a choice of 3000K or 4000K colour temperatures

LED lifespan L70 36,000 hours

Self-test emergency as standard

General Information

Lamp Type	LED
Colour / Finish	White
Emergency	Yes
Self Test	Yes
IP Rating	IP20
IK Rating	IK08
Class Protection	1
Internal / External	Internal
Surface / Recessed / Suspended	Surface/Suspended
Warranty (Years)	5
CE Mark	Yes
Length (mm)	1745
Width (mm)	65
Height (mm)	65

Technical Information

Wattage	41W
Lumens Delivered	4814lm
Lm/W	117lm
CRI	Ra 80
CCT	3000/4000K
Input	220/240V
Hertz	50Hz
Operating Temp	-10°C to 40°C

Technical Data - ETIM - Batten luminaire (EC000109)

With light source	Yes
Suitable for number of lamps	1
Material	Steel
Colour housing	White
Nominal voltage	220-240 V
Control gear included	Yes
No dim function	Yes
Suitable for emergency lighting	Yes
Degree of protection (IP)	IP20
Protection class	I
With movement sensor	No
Max. system power	41 W
Rated luminous flux acc. IEC 62722-2-1	4814 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Width	65 mm
Height/depth	65 mm
Length	1745 mm

Datasheet generated from <https://onetimepim.com> last updated Monday, September 6, 2021 12:40:02 PM

	Code	A	B	C	D
	ATLLED4	1220	600	65	65
	ATLLED5	1525	600	65	65
	ATLLED6	1745	600	65	65
	ATLLED2X4	1220	600	65	65
	ATLLED2X5	1525	600	65	65
	ATLLED2X6	1745	600	65	65