


Tornado EVO


Tornado EVO CCT Multi Wattage 1200mm Code: ATORE4/1

Category	Battens and Weatherproofs	
Application	Ancillary, Commercial, Education, Healthcare,	
Hospitality, Industrial, Retail		
Specification	Performance	









PRODUCT FEATURES

- High efficiency up to 160 Lm/W
- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- LED performance allows point-to-point replacement of existing fluorescent luminaires
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation

GENERAL INFORMATION		
Wattage	20W/40W	
Lumens Delivered	3100lm - 6200lm (4000K)	
Lm/W	160lm/W (4000K)	
Beam Angle	120	
CRI	80	
CCT	4000/5000/6500K	
Input	220/240V	
Operating Temp	-20°C - 40°C	
SDCM	6	
Energy efficiency class	D	

- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

TECHNICAL INFORMATION			
Light Source	LED		
Colour / Finish	Grey		
IP Rating	IP65		
Class Protection	1		
Internal / External	Internal / External		
Surface / Recessed / Suspended	Ceiling, Suspended		
Lumen Depreciation	L70 54,000h		
Warranty (Years)	5		
CE Mark	Yes		
Height	80 mm		