













Tornado EVO


Tornado EVO CCT Multi Wattage 1500mm Code: ATORE5/1











PRODUCT FEATURES

High efficiency up to 160 Lm/W

www.ansell-lighting.com

- CCT selectable between 4000K, 5000K and 6500K and power selectable; offering a choice of 2 outputs, in one luminaire
- LED performance allows point-to-point replacement of existing fluorescent luminaires
- Whole luminaire illuminates during emergency operation rather than a small area, allowing less emergency versions required on an installation
- High efficiency up to 160 Lm/W
- Slim sloped diffuser design creates sleek appearance and offers greater light distribution
- Lockable heavy-duty stainless steel clips supplied as standard for added safety and security

GENERAL INFORMATION		
Wattage	30W/60W	
Lumens Delivered	4700lm - 9300lm (4000K)	
Lm/W	160lm/W (4000K)	
Beam Angle	120	
CRI	80	
CCT	4000/5000/6500K	
Input	220/240V	
Operating Temp	-20°C - 40°C	
SDCM	6	
Energy efficiency class	D	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L70 54,000h	
Warranty (Years)	5	
CE Mark	Yes	
Height	80 mm	