









Battens and Weatherproofs

Hospitality, Industrial, Retail


Performance



Tornado PRO

Tornado PRO Twin 1500mm Microwave Sensor Code: ATORPLED2X5/MWS





Category

Application

Specification



Ancillary, Commercial, Education, Healthcare,

PRODUCT FEATURES

High efficiency up to 161 Lm/W

www.ansell-lighting.com

- Unique base design caters for multiple installation methods
- Quick release LED array / gear tray assembly provides the installer the means to faster installation / maintenance
- Self-test emergency option with Li-ion battery technology, reducing charge time and running costs
- High efficiency up to 161 Lm/W
- Installer friendly embedded features aid accurate and fast installation for any application
- Fast latching / permanently located stainless steel side clips ensure a quick and secure connection
- $_{\bullet}\;$ High output 5ft options available

GENERAL INFORMATION		
Wattage	61W	
Lumens Delivered	6300lm	
Lm/W	103lm/W	
Beam Angle	100/120	
CRI	80	
CCT	4000K	
Input	220/240V	
Operating Temp	-10°C - 40°C	
SDCM	6	

TECHNICAL INFORMATION		
Light Source	LED	
Colour / Finish	Grey	
IP Rating	IP65	
Class Protection	1	
Internal / External	Internal / External	
Surface / Recessed / Suspended	Ceiling, Suspended	
Lumen Depreciation	L80 54,000h	
Warranty (Years)	7	
CE Mark	Yes	
Height	70 mm	
Accessories	ATORPLED/SSKIT/SINGLE,	
	ATORPLED/SSKIT/TWIN	