



Indy K3 65-80-125W

Wattage Switchable Symmetrical Floodlight

Features

IK rating	IK07
IP rating	IP65
CSP Switchable	Single CCT
Tilttable	180°
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	50,000h L70
CRI	80 Ra
SDCM	5 SDCM
Emergency Option	No

Installation information

Install Connector Type	Flying lead
Inrush Current	IFLB1N: 30.3A 0.22ms IFLB2N: 53A 0.22ms IFLB3N: 30.3A 0.22ms
Construction Material	Die-cast aluminium (body) stainless steel 304 (bracket)
Weight	IFLB1N_: 2.5kg IFLB2N_: 4.5kg IFLB3N_: 7.1kg
Maximum Ambient Temperature	-40°C to 40°C
SELV	No
UK Building Regulations	Part P
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
IFLB1N40	Black	80	4000K	120°	12500	156	4401
IFLB1N40	Black	125	4000K	120°	19500	156	6865
IFLB1N30	Black	80	3000K	120°	12000	150	3345
IFLB1N30	Black	125	3000K	120°	19000	152	6689

Wiring information

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately
----------	----------------------------	-----------------



collingwood

01604 495 151
collingwoodlighting.com

collingwoodled

/collingwoodlighting

collingwoodlighting

Guarantee

5 years

Features & benefits

High efficacy up to 156lm/W

Wattage switchable between 65-125W

Suitable for use in coastal applications

Quick and easy installation with angle stamped brackets

Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications

Compatible with the PCELLKIT dusk to dawn sensor

6kV Surge Protection

Asymmetrical floodlights also available in K2 product range

Suitable for use in coastal applications

Light source energy efficiency:



Beam angle: 120°

