



Indy K3 300W

Symmetrical floodlight suitable for commercial and industrial applications

Features

IK rating	IK07
IP rating	IP65
CSP Switchable	Single CCT
Tilttable	180°
Sensor Option	Daylight with accessory
Dimmable Option	No
LED Lifetime	50,000h L70
CRI	80 Ra
SDCM	5 SDCM
Emergency Option	No

Installation information

Install Connector Type	Flying lead
Inrush Current	IFLB1N: 30.3A 0.22ms IFLB2N: 53A 0.22ms IFLB3N: 30.3A 0.22ms
Construction Material	Die-cast aluminium (body) stainless steel 304 (bracket)
Weight	7.1kg
Maximum Ambient Temperature	-40°C to 40°C
SELV	No
UK Building Regulations	Part P
Electric Class (1, 2, 3)	1

Photometrics @ 25°C

Product code	Finish	W	Colour	Beam	lm	lm/W	lx @ 1m
IFLB3N40	Black	300	4000K	120°	44500	138	15420
IFLB3N30	Black	300	3000K	120°	44000	147	15247

Wiring information

Cable / Flying Lead	1000mm H05RN-F 3x1.0mm ² Ø7mm
Type of Wiring Required	Parallel

Accessories

PCELLKIT	Wall Mounted Photocell Kit	Sold Separately
----------	----------------------------	-----------------



01604 495 151
collingwoodlighting.com

- collingwoodled
 /collingwoodlighting
 collingwoodlighting

Guarantee

5 years

Features & benefits

High efficacy up to 147lm/W

Quick and easy installation with angle locking brackets

Suitable for use in coastal applications

Compliant to ISO 9223:2012 C4 classification making the product to be suitable for use in coastal applications

Compatible with the PCELLKIT dusk to dawn sensor

6kV Surge Protection

Asymmetrical floodlights also available in K2 product range

Suitable for use in coastal applications

Light source energy efficiency:



Beam angle: 120°

