

Range	Acti9
Product name	Load centre KQ II B
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Standard
Door type	Overall
Provided equipment	Enclosure Door Front cover Pan assembly Earth terminal block 25 mm ² Shielded neutral bar 25 mm ²

Surface
250 A at 400/415 V AC
Lugs
Switch disconnector - 4P
Terminal block - 4P
MCCB - 4P
RCCB - 30 mA - 4P
RCCB - 100 mA - 4P
RCCB - 300 mA - 4P
Miniature circuit breaker (MCB) (plug-on type) as outgoer
Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type) as outgoer
4 ways (3P) outgoer
top and bottom: knock-out

Cable entry	side: knock-out
Height	484 mm
Width	470 mm
Depth	139 mm

Environment

IP degree of protection IP2x B internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15 cm
Package 1 Width	49 cm
Package 1 Length	49 cm
Package 1 Weight	9.846 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	24
Package 2 Height	100 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	245.2 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes

Contractual warranty

Warranty 18 months

Recommended replacement(s)