

Main Range Acti9 **Product name** Load centre KQ II B Product or component type Distribution board Distribution **Device application** Standard **Enclosure type** Overall Door type **Provided equipment** Enclosure Door Front cover Pan assembly Earth terminal block 25 mm² Shielded neutral bar 25 mm² Complementary **Enclosure** mounting Surface

Enclosure mounting	Surface
[le] rated operational current	250 A at 400/415 V AC
Incomer device options	Lugs
	Switch disconnector - 4P
	Terminal block - 4P
	MCCB - 4P
	RCCB - 30 mA - 4P
	RCCB - 100 mA - 4P
	RCCB - 300 mA - 4P
Protection device options	Miniature circuit breaker (MCB) (plug-on type) as outgoer
	Residual current circuit breaker with overcurrent protection (RCBO) (plug-on type) as outgoer
Number of ways	12 ways (3P) outgoer
Cable entry	top and bottom: knock-out
	side: knock-out
Height	700 mm
Width	470 mm
Depth	139 mm

IP degree of protection IP2x B internal conforming to BS EN 60529 IP3x external conforming to BS EN 60529

Environment

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.5 cm
Package 1 Width	70 cm
Package 1 Length	49 cm
Package 1 Weight	13.65 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	18
Number of Units in Package 2 Package 2 Height	18 100 cm
Package 2 Height	100 cm

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months

Recommended replacement(s)