

Product Code: VPBN162

Luckinslive 425263066

Description: 2 Gang 2 Way 100W Dimmer Switch



### General Information

Plate Dimensions (mm)	88 (W) x 88 (H) x 8 (D)
Dimensions With Gasket (mm)	91 (W) x 91 (H) x 9 (D)
Plate Fixing Centres - Horizontal (mm)	60.3
Style	Victorian
Finish	Black Nickel
Gasket Colour	Black
Materials	Front Plate & Control Button: Stainless Steel Terminals: Brass PCB: Mixed Components Gasket: Nylon
Anti Microbial Certified	No
Operating Voltage (AC)	250
Load Rating (W)	5 - 100
Load Rating Comments	Suitable For LED
Termination Type	Screw
Terminal Size (mm)	Ø3.5
Terminal Capacity - Solid (mm <sup>2</sup> )	2 x 1.5
2 Way Switch	Yes
Switch Control Type	Press - ON/OFF, Rotate - Dim
Dimmer Technology Type	Trailing Edge
Minimum Brightness Programming	Available
Minimum Back Box Depth (mm)	25
Ingress Protection	IP20
Operational Temperature (°C)	-5 to +40
Warranty (Years)	20
	Frequency (Hz) 50
	Terminal Torque Value (Nm) 0.25
	Warranty - Electronics (Years) 2

### Standards

BS EN 60669-1, BS EN 60669-2-1, BS EN 55015, BS EN 61000-3-2

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth. We recommend the use of branded LED lamps with all Deco® trailing edge dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. For further information please contact Click® Technical support team. Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

### Compatible Dimmer Modules

MD9014: 100W Dual Mode LED Dimmer Module  
MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module  
MD9010: 1-10V Analogue Rotary Dimmer Module

