



ATURWOLED/175



Features

High performance LED inground uplight

Exceeds performance of 70W CDM-T

Static load test to 2000kg

Supplied c/w installation housing for additional protection and ease of installation

Die-cast aluminium construction with 316L stainless steel top frame

Pre-wired with 1 metre of rubber insulated cable

LED lifespan L70 50,000 hours

Triac dimmable as standard

General Information

Lamp Type	LED
Colour / Finish	Stainless Steel
IP Rating	IP67
IK Rating	IK10
Class Protection	1
Internal / External	External
Surface / Recessed / Suspended	Recessed
Warranty (Years)	5
CE Mark	Yes
Diameter (mm)	175
Depth (mm)	190

Technical Information

Wattage	8W
Lumens Delivered	884lm
Lm/W	110lm
Beam Angle	18
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20 to 25°C

Technical Data - ETIM - In-ground luminaire (EC000758)

With light source	Yes
Suitable for number of lamps	1
Colour housing	Stainless steel
Nominal voltage	230-230 V
Control gear included	Yes
Beam angle	Narrow beam 11-20°
Degree of protection (IP)	IP67
Protection class	I
Max. system power	8 W
Rated luminous flux acc. IEC 62722-2-1	884 lm
Colour of light	White
Colour temperature	4000-4000 K
Colour rendering index CRI	80-89
Height/depth	190 mm
Outer diameter	175 mm
Max. load	2000 kg

Datasheet generated from <https://onetimepim.com> last updated Friday, February 18, 2022 12:23:45 PM

