



DATASHEET



BATMCW6

230V 6ft 49W Modular CCT and Wattage Adjustable Batten

www.mlaccessories.co.uk



MLA PART CODE	BATMCW6
DESCRIPTION	230V 6ft 49W Modular CCT and Wattage Adjustable Batten
NET WEIGHT (KG)	2
FINISH	White
DIFFUSER	Opal
DIMENSIONS (MM)	Length - 1790 Width - 61 Projection - 70
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
IK RATING	IK08
WATTAGE (W)	28/34/41/49
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	4000/4200/4100,4900/5200/5000,5700/6100/5900,6500/7200/6700
LUMENS LIGHT SOURCE ONLY (LM)	4500/4900/4600,5500/6000/5700,6300/7000/6400,7500/8300/7800
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	173/173/169/168
CIRCUIT WATTAGE (W)	28.3/34.4/41.4/49.2
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	>85
SDCM	<6
RUNNING CURRENT (A)	0.14/0.16/0.19/0.22
SVM	0.01
PST-LM	0.01
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	100000

DIMMABLE	No
EMERGENCY CONVERSION KIT	MODEMKIT
OPERATING TEMPERATURE	-20~45°C
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 50-133V OUTPUT CURRENT - 200/250/300/350mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90 CASE TEMPERATURE (Tc) - 80°C
WARRANTY	7year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5061061272886

Date Created: 06/06/2025 09:44

