

Product Code: CMA162

Luckinslive 425262504

Description: 2 Gang 2 Way 100W Dimmer Switch



General Information

| | | |
|--|--|---|
| Plate Dimensions (mm) | 86 (W) x 86 (H) x 9.5 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | |
| Style | Rounded Profile | |
| Materials | Front Plate: Urea Terminals: Brass PCB: Mixed Components | Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated |
| Anti Microbial Certified | Yes | |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Load Rating (W) | 5 - 100 | |
| Load Rating Comments | Suitable For LED | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø3.5 | Terminal Torque Value (Nm) 0.25 |
| Terminal Capacity - Solid (mm²) | 2 x 1.5 | |
| 2 Way Switch | Yes | |
| Switch Control Type | Press - ON/OFF, Rotate - Dim | |
| Dimmer Technology Type | Trailing Edge | |
| Minimum Brightness Programming | Available | |
| Minimum Back Box Depth (mm) | 25 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 25 | Warranty - Electronics (Years) 2 |

Standards BS EN 60669-1, BS EN 60669-2-1, BS EN 55015, BS EN 61000-3-2

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
We recommend the use of branded LED lamps with all Mode® trailing edge dimmers. The use of inferior, non-branded lamps may require the nominal rating of the dimmer to be reduced. For further information please contact Click® Technical support team.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Compatible Dimmer Modules

MD9014: 100W Dual Mode LED Dimmer Module
MD9001: 6A Push ON/OFF (Dummy Dimmer / Non Dimmable) Module
MD9010: 1-10V Analogue Rotary Dimmer Module

