

Epping

07097 EPP03VER-BLK

Epping, Vertical LED brick light, 3W, 22°, 4000K, Black

- Die-cast aluminium body with polycarbonate front cover
- Choice of styles and mounting positions
- Polycarbonate back box for easy installation
- Black and dark grey textured powder coat finishing



Overview

The Epping LED brick lights are available in versions suitable for ground or wall mounting. Wall mounting horizontal (standard) or vertical. Made from die-cast aluminium with a polycarbonate diffuser the weather resistant brick lights are suited for outdoor areas such as driveways and car parks. Available in black or grey finish.



IP65



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Protection Rating	Class I
Installation Area	Internal and External
L80B10 Lifetime (h) @Ta 25 °C	54,000 h

Compliance

LVD	EN 60598-1:2024, EN 60598-2-1:2021, EN 62031:2020, EN 62493:2015+A1:2022
EMC	EN 55015:2019+A11:2020, EN 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, EN 61547:2023
Others	RoHS, WEEE

Technical Summary

Product Code	EPP03VER-BLK
Input Voltage Supply	220-240Vac 50/60Hz
Inrush Current (peak/duration) (A)	16A / 100µs
Default Power	3 W
Power Factor	0.5
Default CCT	4,000 K
SDCM of CCT	<6
CRI	82
Dimmable	N
Flicker	5%
Lumens Output Maximum	140 lm
Maximum Efficiency	47 lm/W
L70B50 Lifetime (h) @Ta 25 °C	54,000 h
L80B10 Lifetime (h) @Ta 25 °C	54,000 h
L90B10 Lifetime (h) @Ta 25 °C	27,000 h
Nominal Lifetime (h)	50,000 h
Glow wire temperature(°C)	650
Blue Light Hazard	RG1
Weight	0.9Kg
Dimensions (L x W x D) (mm)	232x78.5x116
Beam Angle - Lumi (°)	22

Tel: 01635 523 713

Email: sales@kosnic.com


Kosnic.com



07097 EPP03VER-BLK

Overview

The Epping LED brick lights are available in versions suitable for ground or wall mounting. Wall mounting horizontal (standard) or vertical. Made from die-cast aluminium with a polycarbonate diffuser the weather resistant brick lights are suited for outdoor areas such as driveways and carparks. Available in black or grey finish.



EPP03VER



IP65



General Information

Ambient Temperature Range (°C)	-20°C to 50°C
IK Rating	IK10
IP Rating	IP65
Nominal Lifetime (h)	50,000 h
Protection Rating	Class I
Installation Area	Internal and External

Tel: 01635 523 713

Email: sales@kosnic.com

Kosnic.com

