



Hush ActiV Grade C Domestic Fire Alarm Kit(1 x Hush Controller, 1 x PSU, 3 x ActiV bases, 1 x ActiV Multi sensor, 1 x ActiV smoke detector, 1 x ActiV heat detector and 1 x ActiV base sounder c/w lid & adaptor plate)



Overview

A new Grade C domestic fire detection & alarm system to BS 5839-6 (2019) for use in individual flats, houses and apartments.

Supplied as a cost-effective kit for ease of specification.

Includes a Hush-ActiV central controller, a 230V/24V PSU, one ActiV heat detector, one ActiV smoke detector, one ActiV multi-sensor, three ActiV detector bases and an ActiV alarm sounder (additional ActiV devices available for larger systems).

Monitored for battery, power supply, detector removal & open/short circuit faults.

Low-level system controller facilitates compliance with the Equality Act.

Controller includes a replaceable 72 hour standby battery that lasts over 10 years in normal usage.

Can be used in any situation where Grade D Mains/Battery Alarms are specified.

Kits with a different mix of fire detectors also available.

NEED a Hush system that connects to a landlord system? Enquire about our HUSH-PRO system. [Click here for details.](#)

More Information

HAK/1 kit contents

1 x Hush-ActiV Controller c/w 72 hour standby battery 1 x 24V 250mA PSU

1 x ActiV multi sensor

1 x ActiV smoke detector

1 x ActiV heat detector

3 x ActiV detector bases

1 x ActiV base sounder c/w lid & adaptor plate

Optional decor plates available for use with ceiling mounted ActiV devices to cover the larger hole left when used to retrofit older Grade D alarm devices.

Technical Specifications



T 01942 322744 E sales@c-tec.co.uk

F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



Compatibility	Compatible with C-TEC's ActiV range of conventional fire alarm devices. For the contents of this kit, see Kit Contents section below.
Total output current limited to	100mA
Quiescent current	5mA.
Battery charge capacity	2Ah.
Max battery size and type	2Ah Li-Ion battery supplied (replaceable, up to 10 year life).
No. of detector zone circuits	1.
No. of conventional sounder circuits	1.
Indicators	4 x LEDs on Hush Controller: Supply (green); Fault (yellow); Alarm (red); Hushed (amber).
Controls	1 x TEST button; 1 x HUSH button.
Expansion connections	1 x unmonitored open collector Fire output (follows the dwelling's sounders but ignores system Tests); 1 x unmonitored open collector Fault output; 1 x unmonitored Alarm trigger.
Onboard Sounder	Yes. Provides audible feedback of a fire/fault condition.
Product dimensions (mm)	Hush Controller: 146 W x 85 H x 25 D mm (Can be mounted on a standard UK 35mm double gang flush or surface back box).
Construction & finish	Supplied on a double gang plastic plate.
IP Rating	IP40.
Weight	160g.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.
Kit contents	Includes a Hush-ActiV central controller, a 230V/24V PSU, one ActiV heat detector, one ActiV smoke detector, one ActiV multi-sensor, three ActiV detector bases and an ActiV alarm sounder.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom