



Product Code: MCP022

Luckinslive 437625485

Description: 20A Double Pole Plate Switch With Optional Flex Outlet



General Information

Dimensions (mm)	88 (W) x 88 (H) x 48 (D)		
Plate Fixing Centres - Horizontal (mm)	60,3		
Style	Metal Clad Pro		
Colour	Dusty Grey		
Insert Colour	Polar White		
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert, Switch & Rear Housing:	Urea
	Terminals: Brass	Terminal Screws:	Steel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Brass	Internal Busbars:	Formed Pressed Brass
	Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	20		
Termination Type	Screw	Terminal Torque Value (Nm)	1.2
Terminal Size (mm)	Ø5		
Terminal Capacity - Solid (mm ²)	3 x 2,5 or 2 x 4,0		
Double Pole Switch	Yes		
Twin Earth Terminals	Yes		
Flex Outlet Available	Yes		
Flex Outlet Location	Front of Plate	Flex Outlet Dimension (mm)	Ø10
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	6 x Ø20		
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm)	1 x Ø20
Back Box Knockouts - Left Side (mm)	2 x Ø20	Back Box Knockouts - Right Side (mm)	1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

