



Product Code: MCP034

Luckinslive 437625582

Description: 15A Switched Round Pin Socket Outlet



General Information

| | | |
|--|---|--|
| Dimensions (mm) | 88 (W) x 88 (H) x 48 (D) | |
| Plate Fixing Centres - Horizontal (mm) | 60.3 | |
| Style | Metal Clad Pro | |
| Colour | Dusty Grey | |
| Insert Colour | Polar White | |
| Materials | Front Plate & Mounting Box: Electrophoretically Coated Steel | Insert: Urea |
| | Terminals: Brass | Terminal Screws: Steel & Yellow Passivated |
| | Internal Busbars: Formed Pressed Brass | Earth Strap: Mild Steel |
| Operating Voltage (AC) | 250 | Frequency (Hz) 50 |
| Resistive Load Rating (A) | 15 | |
| Termination Type | Screw | |
| Terminal Size (mm) | Ø5 | Terminal Torque Value (Nm) 2 |
| Terminal Capacity - Solid (mm²) | 4 x 1.5 or 3 x 2.5 | |
| Switched | Yes | |
| Single Pole Switched | Yes | |
| Twin Earth Terminals | No | |
| Supplied Back Box Depth (mm) | 40 | |
| Back Box Knockouts - Total (mm) | 6 x Ø20 | Back Box Knockouts - Bottom (mm) 1 x Ø20 |
| Back Box Knockouts - Top (mm) | 1 x Ø20 | Back Box Knockouts - Right Side (mm) 1 x Ø20 |
| Back Box Knockouts - Left Side (mm) | 2 x Ø20 | |
| Back Box Knockouts - Rear (mm) | 1 x Ø20 | |
| Ingress Protection | IP20 | |
| Operational Temperature (°C) | -5 to +40 | |
| Warranty (Years) | 20 | |

Standards BS 546

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.
All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Catalogue



Range



DoC



Installation

