



Product Code: MCP039BK

Luckinslive 437625663

Description: 2A Round Pin Socket Outlet



**General Information**

Dimensions (mm)	88 (W) x 88 (H) x 48 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Metal Clad Pro		
Colour	Black		
Insert Colour	Black		
Materials	Front Plate & Mounting Box:	Insert: Urea	
	Electrophoretically Coated Steel	Terminal Screws:	Steel & Yellow Passivated
	Terminals: Brass	Earth Strap:	Mild Steel
	Internal Busbars: Formed Pressed Brass	Frequency (Hz)	50
Operating Voltage (AC)	250		
Resistive Load Rating (A)	2		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	1.2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 1.5 or 2 x 2.5		
Switched	No		
Twin Earth Terminals	No		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	6 x Ø20	Back Box Knockouts - Bottom (mm)	1 x Ø20
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Right Side (mm)	1 x Ø20
Back Box Knockouts - Left Side (mm)	2 x Ø20		
Back Box Knockouts - Rear (mm)	1 x Ø20		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

**Standards** BS 546

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.  
 All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Catalogue



Range



DoC



Installation

