



Product Code: MCP530PW

Luckinslive 437624790

Description: 13A 1 Gang Unswitched Socket Outlet



General Information

Dimensions (mm)	88 (W) x 88 (H) x 48 (D)	
Plate Fixing Centres - Horizontal (mm)	60,3	
Style	Metal Clad Pro	
Colour	Polar White	
Insert Colour	Polar White	
Materials	Front Plate & Mounting Box:	Insert & Rocker Switch: Urea
	Electrophoretically Coated Steel	Terminals: Brass
	Rear Housing: Urea	Internal Busbars: Formed Pressed Brass
	Terminal Screws: Steel & Yellow Passivated	
	Earth Strap: Mild Steel	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø4,8	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2,5 or 2 x 4	
Switched	No	
3 Pin Safety Shuttered	Yes	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	6 x Ø20	Back Box Knockouts - Bottom (mm) 1 x Ø20
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Right Side (mm) 1 x Ø20
Back Box Knockouts - Left Side (mm)	2 x Ø20	
Back Box Knockouts - Rear (mm)	1 x Ø20	
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS 1363-2

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

