



Product Code: MCP532BK

Luckinslive 437624813

Description: 13A 2 Gang Unswitched Socket Outlet



General Information

Dimensions (mm)	148 (W) x 88 (H) x 48 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Metal Clad Pro		
Colour	Black		
Insert Colour	Black		
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert & Rocker Switch:	Urea
	Rear Housing:	Terminals:	Brass
	Terminal Screws: Steel & Yellow Passivated	Internal Busbars:	Formed Pressed Brass
	Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw	Terminal Torque Value (Nm)	12
Terminal Size (mm)	Ø4.8		
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Switched	No		
3 Pin Safety Shuttered	Yes		
Twin Earth Terminals	Yes		
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	8 x Ø20	Back Box Knockouts - Bottom (mm)	3 x Ø20
Back Box Knockouts - Top (mm)	2 x Ø20	Back Box Knockouts - Right Side (mm)	1 x Ø20
Back Box Knockouts - Left Side (mm)	1 x Ø20		
Back Box Knockouts - Rear (mm)	1 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS 1363-2

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

