

Product Code: MCP535

Luckinslive 437624839

Description: 13A 1 Gang Double Pole Switched Socket Outlet



General Information

Dimensions (mm)	88 (W) x 88 (H) x 48 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Metal Clad Pro	
Colour	Dusty Grey	
Insert Colour	Polar White	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Insert & Rocker Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel Frequency (Hz) 50
Operating Voltage (AC)	250	
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Double Pole Switch	Yes	
3 Pin Safety Shuttered	Yes	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	6 x Ø20	
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm) 1 x Ø20
Back Box Knockouts - Left Side (mm)	2 x Ø20	Back Box Knockouts - Right Side (mm) 1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20	
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS 1363-2

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

