

Product Code: MCP660

Luckinslive 437625032

Description: 20A Double Pole 1 Gang Plate Key Lockable Switch



General Information

Dimensions (mm)	88 (W) x 88 (H) x 48 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Metal Clad Pro	
Colour	Dusty Grey	
Insert Colour	Polar White	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel Earth Plate & Yoke: Mild Steel Terminal Screws: Steel & Yellow Passivated	Insert: Urea Terminals: Brass GridPro Module: GM2018PW
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Termination Type	Screw	
Terminal Size (mm)	Ø4.8	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm²)	3 x 2.5 or 2 x 4	
Switched	Yes (via Key)	
Modular Rocker Switches	Yes	
Double Pole Switch	Yes	
Twin Earth Terminals	Yes	
Product Marking	On & Off	
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	6 x Ø20	
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm) 1 x Ø20
Back Box Knockouts - Left Side (mm)	2 x Ø20	Back Box Knockouts - Right Side (mm) 1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20	
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

Standards BS EN 60669-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Two keys provided (Spare keys available: SP660)

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

