



Product Code: MCP835

Luckinslive 437625061

Description: 13A 1 Gang Double Pole Switched Socket Outlet With LED



**General Information**

Dimensions (mm)	88 (W) x 88 (H) x 48 (D)	
Plate Fixing Centres - Horizontal (mm)	60,3	
Style	Metal Clad Pro	
Colour	Dusty Grey	
Insert Colour	Polar White	
Materials	Front Plate & Mounting Box:	Insert: Urea
	Electrophoretically Coated Steel	LED Lens: Polycarbonate
	Rear Housing: Urea	Terminal Screws: Steel & Yellow Passivated
	Terminals: Brass	Internal Busbars: Formed Pressed Brass
	Contacts: Silver "on-lay" Copper / Brass	
Earth Strap: Mild Steel		
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Termination Type	Screw	
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm) 2
Terminal Capacity - Solid (mm <sup>2</sup> )	3 x 2,5 or 2 x 4	
Double Pole Switch	Yes	
3 Pin Safety Shuttered	Yes	
LED Indicator	Yes	Indicator Colour Red
Supplied Back Box Depth (mm)	40	
Back Box Knockouts - Total (mm)	6 x Ø20	
Back Box Knockouts - Top (mm)	1 x Ø20	Back Box Knockouts - Bottom (mm) 1 x Ø20
Back Box Knockouts - Left Side (mm)	2 x Ø20	Back Box Knockouts - Right Side (mm) 1 x Ø20
Back Box Knockouts - Rear (mm)	1 x Ø20	
Back Box Earth Terminal Supplied	Yes	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

**Standards** BS 1363-2

**Additional Information**

LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.



Catalogue



Range



DoC



Installation

