

Product Code: MCP840RD

Luckinslive 437625197

Description: 13A 2 Gang Double Pole Switched Socket Outlet With Outboard Rockers & LEDs



General Information

Dimensions (mm)	148 (W) x 88 (H) x 48 (D)		
Plate Fixing Centres - Horizontal (mm)	120.6		
Style	Metal Clad Pro		
Colour	Dusty Grey		
Insert Colour	Polar White		
Switch Finish	Red		
Materials	Front Plate & Mounting Box:		Insert: Urea
	Electrophoretically Coated Steel		LED Lens: Polycarbonate
	Rear Housing: Urea		Terminal Screws: Steel & Yellow Passivated
	Terminals: Brass		Internal Busbars: Formed Pressed Brass
	Contacts: Silver "on-lay" Copper / Brass		
Earth Strap: Mild Steel			
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)	13		
Termination Type	Screw		
Terminal Size (mm)	Ø5	Terminal Torque Value (Nm)	2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4		
Double Pole Switch	Yes		
3 Pin Safety Shuttered	Yes		
Twin Earth Terminals	Yes		
LED Indicator	Yes	Indicator Colour	Red
Supplied Back Box Depth (mm)	40		
Back Box Knockouts - Total (mm)	8 x Ø20	Back Box Knockouts - Bottom (mm)	3 x Ø20
Back Box Knockouts - Top (mm)	2 x Ø20	Back Box Knockouts - Right Side (mm)	1 x Ø20
Back Box Knockouts - Left Side (mm)	1 x Ø20		
Back Box Knockouts - Rear (mm)	1 x Ø20		
Back Box Earth Terminal Supplied	Yes		
Ingress Protection	IP20		
Operational Temperature (°C)	-5 to +40		
Warranty (Years)	20		

Standards BS 1363-2

Additional Information

LED Indicators are not designed to withstand insulation resistance testing at 500V. Carrying out insulation resistance testing at 500V may result in damage to the LED indicator. Please disconnect prior to insulation resistance testing.
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

