



Product Code: MD004PW

Luckinslive 389101727

Description: 10AX 2 Way Retractive Switch Module



## General Information

Dimensions (mm)	25 (W) x 53 (H) x 20 (D)	
Colour	Polar White	
Materials	Rocker Switch:	Urea
	Terminals:	Brass
	Contacts:	Silver "on-lay" Copper / Brass
Anti Microbial Certified	Yes	
Operating Voltage (AC)	250	Frequency (Hz) 50
Inductive Load Rating (AX)	10	
Load Rating Comments	Suitable for Fluorescent or Inductive Loads	
Termination Type	Screw	
Terminal Size (mm)	Ø3,5	Terminal Torque Value (Nm) 0,5
Terminal Capacity - Solid (mm <sup>2</sup> )	4 x 1,5 or 2 x 2,5	
Modular Rocker Switches	Yes	
2 Way Switch	Yes	
Retractive Contact Options	Press to Make or Break	
Minimum Back Box Depth (mm)	16 (25 Flat Plate)	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	

**Standards** BS EN 60669-1

## Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

Suitable and matches the Definity, Mode, Polar & Part M ranges



Catalogue



Range



DoC



Installation

