



# AFDD

- Combined AFDD and RCBO
- Provides Arc Fault protection alongside overcurrent, short circuit, residual current and over-voltage protection
- Class A, 30mA RCD
- Single module 18mm width device, fully interchangeable with Switched and un-switched Neutral RCBO's, and single pole MCB's
- Provides LED fault identification on reset
- Double Pole Switching for complete isolation in the event of a fault
- Switched Neutral pole significantly reduces the installation and commissioning time
- Available in current ratingsd from 6-40A
- B curve overcurrent
- 6kA short circuit breaking capacity
- Suitable for TN & TT earthing systems
- Conforms to BS EN62606 (AFDD) and BS EN61009-1 (RCBO)



## P04-B10/30/1PNA

| TECHNICAL DATA   |         | REGISTRY            |               |
|------------------|---------|---------------------|---------------|
| Rated current    | 10A     | Net weight          | 0.17KG        |
| Trip curve       | B       | Min order quantity  | 1             |
| RCD Class        | A       | EAN Code            | 5026992046159 |
| Residual Current | 30mA    | Gross Weight        | 0.19KG        |
| Frequency        | 50/60Hz | REFERENCE STANDARDS |               |
| Modules Number   | 1       | STANDARDS           |               |
|                  |         | BS EN 61009-1       |               |