Xnightsbridge


DATASHEET



RE6CTF

RenuLED Fixed - 6W IP65 Fire-rated LED Downlight with 3 x CCT

www.mlaccessories.co.uk



| MLA PART CODE | RE6CTF |
|-------------------------------|--|
| DESCRIPTION | RenuLED Fixed - 6W IP65 Fire-rated LED Downlight with 3 x CCT |
| NET WEIGHT (KG) | 0.146 |
| FINISH | White |
| DIMENSIONS (MM) | Diameter - 86 Projection - 2 Overall Height - 50 Recessed Depth - 48 Minimum Void - 48 |
| CUT-OUT (MM) | Cut-out Diameter - 55-70 |
| CONSTRUCTION | Construction - Pressed steel Construction 2 - & polycarbonate |
| CLASS | II |
| IP RATING | IP65 (IP20 from above) |
| WATTAGE (W) | 6 |
| LAMP TECHNOLOGY | SMD LED |
| LAMP INCLUDED | Yes |
| LUMENS (LM) | 575/635/595 |
| LUMENS LIGHT SOURCE ONLY (LM) | 665 |
| LUMEN TOLERANCE | 5% |
| EFFICACY (LM/W) | 115 |
| CIRCUIT WATTAGE (W) | 5.76 |
| ССТ | 3000/4000/6500K |
| LIGHT COLOUR | CCT |
| CRI | >80 |
| SDCM | <6 |
| RUNNING CURRENT (A) | 0.02944 |
| DISPLACEMENT FACTOR | >0.7 |
| SVM | 0.001 |
| PST-LM | 0.013 |





Xnightsbridge

| BEAM ANGLE (DEGREES) | 55 |
|--|----------------------------|
| LIFE SPAN (HRS) | 30,000 |
| L70B50 LIFESPAN (HRS) | 30,000 |
| DIMMABLE | Yes* |
| FIRE-RATED | Tested to 30/60/90 minutes |
| I-JOIST RATED | 30 minutes |
| WEB-JOIST RATED | 30 minutes |
| IC RATED | Yes |
| ACOUSTIC RATED | Yes |
| OPERATING TEMPERATURE | 25°C |
| INPUT VOLTAGE | 230V 50Hz |
| CABLE LENGTH (M) | 0.15 |
| WARRANTY | 3year(s) |
| MANUFACTURED IN ACCORDANCE WITH | BS EN 60598 |
| ORIGIN OF MANUFACTURE | China |
| DECLARATION OF CONFORMITY (HELD ON FILE) | Yes |
| EAN | 5056270851373 |
| Data Created: 06/06/2025 00:17 | |

Date Created: 06/06/2025 09:17





