

Technical Specification

Product Code: CMA30651

Description: 13A Zigbee Smart Switched Fused Connection Unit



General Information

Dimensions (mm)	86 (W) x 86 (H) x 9 (D)	
Dimensions With Gasket (mm)	86 (W) x 86 (H) x 20.5 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Rounded Profile	
Finish	Polar White	
Gasket Colour	Polar White	
Materials	Front Plate: Urea	Rear Housing: Nylon
	Terminals: Brass	Terminal Screws: Steel & Yellow Passivated
	Internal Busbars: Formed Pressed Brass	Electronics: PCB & Electronic Components
	Gasket: Polycarbonate	
Anti Microbial Certified	Yes	
Rated Voltage (V~) (Ue)	240	Frequency (Hz) 50
Resistive Load Rating (A)	13	
Fuse Fitted Rating & Type	13A (BS 1362)	
Termination Type	Screw	
Terminal Size (mm)	5.7 x 4.8	Terminal Torque Value (Nm) 1.2
Terminal Capacity - Solid (mm ²)	3 x 2.5 or 2 x 4	
Single Pole Switched	Yes	
Twin Earth Terminals	No	Indicator Colour White & Orange
Minimum Back Box Depth (mm)	25 (With Gasket) 35 (Without Gasket)	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	3	
Standards	BS 1363-4 & BS 1362 BS EN 61000-6-1 BS EN 61000-6-3 BS EN 60669-2-1 in conjunction with BS EN 60669-1	

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.
Zigbee signal mesh
Enables manual control (unless locked), wireless control and automated control
Voice control via ClickSmart+ Hub using Alexa and/or Google Home