

Product Code: MC20211

Description: 2 Pole 1 Module 20A Contactor, 1 x Normally Open, 1 x Normally Closed Contacts



General Information

Dimensions (mm)	18 (W) x 106 (H) x 68 (D)	
Finish	Light Grey (RAL 7035)	
Rated Operational Voltage (V~) (Ue)	250	
Frequency (Hz)	50/60	
Rated Operating Current - AC-1 / AC-7a (A)	20	
Rated Operating Current - AC-1 / AC-7b (A)	7	
Rated Insulation Voltage (V) (Ui)	500	
Endurance Mechanical Operations	>5000000	
Endurance Electrical Operations	>100000	
Device Terminals	Screwed Lug & Pin	
Coil Terminal Capacity - Flexible (mm²)	1.5 to 2.5	Coil Terminal Torque - Flexible (Nm) 0.8
Coil Terminal Capacity - Rigid (mm²)	1.5 to 2.5	Coil Terminal Torque - Rigid (Nm) 0.8
Main Contact Terminal Capacity - Flexible (mm²)	1 to 4	Main Contact Terminal Torque - Flexible (Nm) 0.9
Main Contact Terminal Capacity - Rigid (mm²)	1.5 to 6	Main Contact Terminal Torque - Rigid (Nm) 0.1
Number Of Poles	2	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +60	
Warranty (Years)	3	

Standards BS EN 60947-4-1, BS EN 61095

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.

Termination Layout

