

Product Code: PRW208 Description: 10A 3 Pole Fan Isolation Pull Cord Switch



General Information

Dimensions (mm)	86 (W) x 86 (H) x 43 (D)	
Plate Fixing Centres - Horizontal (mm)	60.3	
Style	Square Edge	
Finish	Polar White	
Materials	Front Plate: Urea Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Earth Strap: Mild Steel	Terminal Housing: Urea Terminals: Brass Internal Busbars: Formed Pressed Brass Pull Bell: Urea
Anti Microbial Certified	Yes	
Rated Voltage (V~) (Ue)	250	Frequency (Hz) 50
Resistive Load Rating (A)	10	
Termination Type	Screw	
Terminal Size (mm)	Ø4.5	Terminal Torque Value (Nm) 0.4
Terminal Capacity - Solid (mm²)	2 x 1.5 or 1 x 2.5	
Triple Pole Switch	Yes	
Twin Earth Terminals	Yes	
Minimum Back Box Depth (mm)	25	
Ingress Protection	IP20	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	20	
Standards	BS EN 60669-1	

Additional Information	<p>For cleaning / polishing of products, use only a soft, dry, clean cloth.</p> <p>Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.</p> <p>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.</p> <p>All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.</p> <p>All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.</p>
------------------------	--