


Product Code: TPEB4

Description: 4 Way 125A Three Phase Distribution Board without Incomer



General Information

Dimensions With Door (mm)	450 (W) x 500 (H) x 140 (D)	
Colour	White	
Materials	Enclosure & Cover: Powder Coated Steel	Pan Assembly / Chassis: Steel
	Plastic Components: ABS & Polycarbonate	
Rated Operational Voltage (AC) (Ue)	230/400	
Frequency (Hz)	50/60	
Busbar Current Rating (A)	125	
Busbar Rating (kA)	25	
Maximum Rated Current (A) (In)	125	
Total Ways	4 (TP), 12 (SP)	
E&N Terminals	Screw	
E&N Bars Capacity (mm²)	25	E&N Bars Torque (Nm) 2
Earth Lug Size	M8	Earth Lug Torque (Nm) 4
Input Terminal Capacity - Rigid (mm²)	50	
Output Terminal Capacity - Rigid (mm²)	25	
Max Cable Tie Width (mm)	8	
Gland PLate	Top & Bottom Removal	
Fire Resistance	650°C / 30s	
Fire Resistance Current Carrying Parts	960°C/30s	
Impact Rating	IK05	
Ingress Protection	IP3X	
Maximum Humidity (%)	95	
Storage Temperature (°C)	-40 to +75	
Operational Temperature (°C)	-5 to +40	
Warranty (Years)	10	Warranty - Devices (Years) 3

Standards BS EN 61439-3

Additional Information For cleaning / polishing of products, use only a soft, dry, clean cloth.
Elucian metal distribution boards allow compliance with BS 7671 Wiring Regulations

Compatible Accessories

- TP2SP: Three Phase to Single Phase converter
- TP125CAP: 125A busbar caps (10)
- TPSRBP: Synthetic Bonded Resin Paper with Slot
- TPPLATE: Gland Plate
- TPLABELK: Label Pack
- TPLOCK: Three Phase Isolator Locking Kit
- TPRCDLINK: Three phase RCD Link Kit

